

## **INSTALLATION APPLICATIONS**

GRI's 3/8" recessed press-to-fit contacts can be installed in many different positions to accommodate a variety of applications. The switch and magnet can be mounted end-to-end within an imaginary arc around the switch, or parallel to the switch. When the application calls for a wide gap switch, install the painted end of the bare magnet facing the switch as they are polarity sensitive. The switch and magnet should never form a "T" configuration when installed.

If this series is to be used in a steel door application, GRI's PA-75 adapter should be used with a wide gap switch.

WARRANTY: Lifetime warranty against workmanship, material and factory defects.

GEORGE RISK INDUSTRIES, INC. G.R.I. PLAZA KIMBALL, NE 69145



1-800-445-5218 1-800-523-1227 (308) 235-4645 FAX (308) 235-3561 E-MAIL: sales@grisk.com

WWW.GRISK.COM



.375 in

(9.53 mm)

2020-T

.441 in

(11.18 mm)

.441 in Terminals / .375 in (11.18 mm) (9.53 mm)

1.25 in

(31.75 mm)

## **GRI PRODUCTS MEET OR EXCEED THESE MINIMUM GENERAL SPECIFICATIONS:**

		Electrical	Reed	Max. Initial	Max. Contact		Max. Switching
Part Number	Loop Type	Configuration	Form	Contact Resistance	Rating	Voltage	Current
				(Ω)	(W)	(VDC)	(A)
2020-12	Closed	N/0	А	.150	10	200	.500
2020-12WG	Closed	N/0	А	.150	10	200	.400
2020-12XWG	Closed	N/0	А	.150	10	200	.400
2020-T	Closed	N/0	А	.150	10	160	.400
2020-TWG	Closed	N/0	А	.150	10	160	.400
2020-TXWG	Closed	N/0	А	.150	10	160	.400
3030-12	Open	N/C	В	.140	5	175	.250
3030-12WG	Open	N/C	В	.140	5	175	.250
3030-12XWG	Open	N/C	В	.140	5	175	.250
3030-T	Open	N/C	В	.140	5	175	.250
3030-TWG	Open	N/C	В	.140	5	175	.250
3030-TXWG	Open	N/C	В	.140	5	175	.250
4040-12	Open/Closed	SPDT	С	.140	5	175	.250
4040-12WG	Open/Closed	SPDT	С	.140	5	175	.250
4040-12XWG	Open/Closed	SPDT	С	.140	5	175	.250
4545-12		DPDT	Cx2	.140	5	175	.250
4545-12WG		DPDT	Cx2	.140	5	175	.250

WARRANTY: Lifetime warranty against workmanship, material and factory defects.

GEORGE RISK INDUSTRIES, INC. **G.R.I. PLAZA** KIMBALL, NE 69145

(15.24 mm)

.441 in

(11.2 mm)

.35 in

(8.89 mm)



1-800-445-5218 1-800-523-1227 (308) 235-4645 FAX (308) 235-3561 E-MAIL: sales@grisk.com

WWW.GRISK.COM